TRIPLETT

New!!!

The New, Improved Model 1101-A

Compact DMM



CE

3 Year Warranty

FEATURES

- 3 1/2 Digit, w/ 1999 max. reading
- Backlit Display
- AC/DC Voltage to 500V
- AC/DC Current to 10A
- Temperature Test (Probe Included)
- Resistance to 20MΩ
- Continuity Test
- Diode Check
- Data Hold
- Overload Protection
- Double Insulated Case
- CAT I and II Rated
- Red Rubber Boot w/ Stand
- Safety Test Leads w/ Screw-on Alligator Clips
- Three Year Warranty



Cat. No. 1101

$42.00*

Model 1101-A Specifications

FUNCTIONS	DC Voltage		4(200mV to 200V) 0.5% + 2dgt 1(500V) 0.8% + 2dgt
	AC Voltage		2(200V & 500V) 1.2% +10dgt
	DC Current		2(2000µA to 20mA) 1.0% +2dgt 1(200mA) 1.2% +2dgt 1(10A) 2.0% +5dgt
	Resistance		4(200Ω to 200KΩ) 0.8% +2dgt 1(20MΩ) 1.0% +5dgt
	Temperature Test (K-type)		(-40° to 302°F) ±1.0% +3dgt (303° to 1832°F) ±1.5% +15dgt
	Continuity		≤ 70Ω
	Diode Check		▲
	Transistor Check (hFE)		▲
	Total Ranges / Functions		20
SAFETY	Overload Protection	mV Ranges	230mV DC (500V AC/DC)
		Voltage Ranges (Except mV)	CAT I 600V (IEC 1010-1) CAT II 300V (IEC 1010-1)
		Ω Ranges	500V AC/DC
		Diode Test	500V AC/DC
		Continuity Beeper	500V AC/DC
	Fuses	mA Jack	300mA/250V Fuse
		10A Jack	Unfused
	Agency Approval		CE IEC 1010-1 (EN 61010-1) on Voltage Ranges Only. See "Overload Protection" above
FEATURES	Range Selection		Manual Range
	Digital Display		3 1/2 Digit, 1999 Count
	Backlit Display		▲
	Data Hold		▲
	Auto Polarity		▲
	Low Battery Indication		▲
PHYSICAL	Battery		1 - 9 Volt
	Dimensions (including boot)		3.1 x 5.4 x 1.6 in.
	Weight (including boot)		0.55 lbs.

** Price is Suggested U.S. List.*
All Specifications are PRELIMINARY and are subject to change without notice.
Model 1101-A replaces Model 1101 (Catalog Number remains 1101)

TRIPLETT

Triplett Corporation One Triplett Drive Bluffton, OH 45817
Phone: 800-TRIPLETT Fax: 419-358-7956
www.triplett.com