OMEGAETTE™ HHM221 Mini Current Clamp Meter

HHM221

$60

1 YEAR WARRANTY CE

- Pocket Size
- DATA HOLD Function
- Autoranging



Specifications

Numerical Display: 3½ digital liquid crystal (LCD), Maximum reading 1999
Battery Life: 300 hr approx.
Low Battery Indication: The low battery indicator light is displayed as needed.
Sampling: 2 Times/sec.
Power Source:
1.5V, Size AAA battery X 2 (included)
Operation Temperature and Humidity:
0 to 40°C (32 to 104°F) below 80%RH
Storage Temperature and Humidity:
-10 to 60°C (14 to 140°F) below 70% RH
Rating: IEC 1010; 300 V CAT III;
600 V CAT II
Jaw Opening Diameter: Cables 25 mm (1")
Dimensions: 187 L x 50 W x 29 mm H
(7.36 x 1.97 x 1.14")
Weight: Approx. 210 g (0.46 lb)

Electrical Specifications

ACA Function (Autorange)		
Range	**Resolution**	**Accuracy**
200 A	0.1 A	±2% rdg + 5 dgts
400 A	1 A	

ACV Function (Autorange)		
Range	**Resolution**	**Accuracy**
200 V	0.1 V	±1.5% rdg + 5 dgts
600 V	1 V	

Ohm Function		
Range	**Resolution**	**Accuracy**
200 Ω	0.1 Ω	±1.9% rdg + 3 dgts

Continuity	
Range	**Active Sound Level**
)))	≤100 Ω

AVAILABLE FOR FAST DELIVERY!

To Order *(Specify Model)*		
Model Number	**Price**	**Description**
HHM221	**$60**	Mini current clamp meter
HHM-NIST	**55**	NIST traceable calibration certificate

Unit includes free carrying case, two AAA batteries, test leads, and complete operator's manual.
Ordering Example: HHM221**, mini current clamp meter, **$60.

omega.com®

Your One-Stop Source for Process Measurement and Control!

One Omega Drive | Stamford, CT 06907 | 1-888-TC-OMEGA (1-888-826-6342) | info@omega.com

www.omega.com

UNITED STATES
www.omega.com
1-800-TC-OMEGA
Stamford, CT.

UNITED KINGDOM
www. omega.co.uk
Manchester, England
0800-488-488

CANADA
www.omega.ca
Laval(Quebec)
1-800-TC-OMEGA

FRANCE
www.omega.fr
Guyancourt, France
088-466-342

GERMANY
www.omega.de
Deckenpfronn, Germany
0800-8266342

CZECH REPUBLIC
www.omegaeng.cz
Karviná, Czech Republic
596-311-899

BENELUX
www.omega.nl
Amstelveen, NL
0800-099-33-44



More than 100,000 Products Available!

• Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

• Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

• pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

• Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

• Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters

• *click here to go to the omega.com home page* •