PD-130/131/132

PD-130



¡ECONOMIC!

PD-131



DANGEROUS VOLTAGE INDICATOR

PD-132



¡AUTORANGE!

SPECIFICATIONS	PD-130	PD-131	PD-132
LCD indicator	3 1/2 digits, 1999 points	3 1/2 digits, 1999 points	3 3/4 digits, 3200 points
Analog bargraph	–	–	34 segments
DC voltage	2 V, 20 V, 200 V, 600 V	200 mV, 2 V, 20 V, 600 V	320 mV, 3,2 V, 32 V, 320 V, 600 V
AC voltage	200 V, 600 V	200 mV, 2 V, 20 V, 600 V	320 mV, 3,2 V, 32 V, 320 V, 600 V
DC current	200 µA, 2 mA, 20 mA, 20 mA, 10 A	200 µA, 20 mA, 200 mA, 10 A	320 µA, 3200 µA, 32 mA, 320 mA10 A
AC current	–	200 µA, 20 mA, 200 mA, 10 A	320 µA, 3200 µA, 32 mA, 320 mA10 A
Resistance (Ω)	200, 2 k, 20 k, 200 k, 20 M	200, 20 k, 200 k, 20 M	320, 3.2 k, 32 k, 320 k, 3.2 M, 30 M
Diode test	Yes	Yes	Yes
Battery test	Yes	Yes	Yes
Continuity audible Indication	–	Yes	Yes
Basic accuracy	± (2.0% read. + 1 digit)	± (1.2% read. + 1 digit)	± (0.8% read. + 1 digit)
Data Hold	–	Yes	Yes
Auto power-off	–	–	Yes
Maximum voltage	600 V DC or AC rms	600 V DC or AC rms	600 V DC or AC rms
Input protection	Fast fuse	Fast fuse	Fuse
Dang. voltage indicator		From 70 to 480 V AC	
Battery file	300 hours	200 hours	500 hours
Included accessories	Test leads Instructions manual, 9 V Battery	Test leads Instructions manual, 9 V Battery	Test leads Instructions manual, 9 V Battery